


SCHEDULE 80 PVC



Тее				
Part No	Size (in)	L	Н	G
801-002	1⁄4	1 7/8	15/16	5/16
801-003	3/8	2 5/16	1 5/32	13/32
801-005	1/2	2 25/32	1 3/8	1/2
801-007	3⁄4	3 5/32	1 9/16	9/16
801-010	1	3 25/32	1 7/8	23/32
801-012	1¼	4 9/32	2 5/32	7/8
801-015	1½	4 25/32	2 3/8	1 1/32
801-020	2	5 17/32	2 25/32	1 9/32
801-025	21⁄2	6 17/32	3 1/4	1 1/2
801-030	3	7 7/16	3 3/4	1 27/32
801-040	4	9 1/8	4 19/32	2 11/32
801-060	6	13	6 9/16	3 9/16
801-080	8	18 5/32	9 5/32	4 21/32
801-100	10	22	11 1/32	6
801-120	12	26 1/4	13 5/32	7 5/32

Headquarters

414 Morgan Street P.O. Box 116 Brownsville, TN 38012 731-772-3180 800-776-2756 Fax: 731-772-0835

Service Centers

5700 East 39th Avenue Denver, CO 80207 303-575-6701 800-824-3675 Fax: 303-575-6706

14820 Carmenita Road, Unit B Norwalk, CA 90650 714-690-9679 800-995-2726 Fax: 714-736-1780

10350 Beaudin Blvd, Suite 600 Woodridge, IL 60517 630-597-0150 888-995-7414 Fax: 630-597-0156

6800 Kingspointe Parkway, Suite 400 Orlando, FL 32819-8588 407-206-5705 800-437-3155 Fax: 407-515-6542

1600 Kelly Blvd., Suite 13/X30 Carrollton, TX 75006 972-417-0073 800-642-8104 Fax: 972-417-9733

325 Lasley Avenue Wilkes Barre, PA 18706-1424 570-301-1170 800-882-5462 Fax: 570-301-1176

8212 South 228th Street Kent, WA 98032 425-272-0990 888-285-2726 Fax: 425-272-0995

Limited Warranty

LASCO Fittings, Inc. products are warranted to be free from manufacturing defects in materials and workmanship. They are warranted against rot, rust, and electrolytic corrosion for a period of three years from date of installation. If LASCO products prove defective due to manufacturing defects in material or workmanship during that period, the manufacturer will provide new replacement units of the same type and size. No remedy will be granted under this warranty if LASCO products are not used strictly in accordance with LASCO's directions with respect to use and storage or if the products have been modified in any way. THE MANUFACTURER'S LIABILITY UNDER EXPRESSED OR IMPLIED WARRANTY OR FOR ANY REASON IS LIMITED TO FURNISHING REPLACE-MENT UNITS OR GRANTING A CREDIT FOR DEFECTIVE UNITS. NO LABOR EXPENSE OR CONSEQUENTIAL DAMAGES WILL BE PAID BY LASCO. THIS WARRANTY IS IN LIEU OF ALL OTHER GUARANTEES AND WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PURPOSE, EXCEPT FOR ANY WARRANTIES IMPLIED BY LAW FOR NONCOMMERCIAL CONSUMERS. ANY SUCH WARRANTIES ARE LIMITED TO THE DURATION OF THIS WRITTEN WARRANTY.

DO NOT USE LASCO FITTINGS FOR COMPRESSED AIR OR GASES. DO NOT TEST PVC PIPING SYSTEMS WITH COMPRESSED AIR OR GASES. DO NOT USE FITTINGS WITH LIQUIDS NOT RECOMMENDED BY LASCO. MODIFICATIONS OF FITTINGS VOIDS THE WARRANTY.

STANDARDS AND SPECIFICATIONS - Schedule 80

- ASTM D-1784 Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly (Vinyl Chloride) (CPVC) Compounds.
- ASTM D-2464 Threaded Poly (Vinyl Chloride) (PVC) Plastic Pipe Fittings, Schedule 80.
- ASTM D-2467 Socket Type Poly (Vinyl Chloride) (PVC) Plastic Pipe Fittings, Schedule 80.
- ASTM F-1970 Standard Specification for Special Engineered Fittings, Appurtenances or Valves for use in Poly (Vinyl Chloride) (PVC) or Chlorinated Poly (Vinyl Chloride) (CPVC) Systems.
- MATERIAL LASCO Schedule 80 Fittings are produced from PVC Type 1, Cell Classification 12454- B.
 - O-Rings are produced from a fluorocarbon elastomer (VITON).
- LISTINGS NSF (National Sanitation Foundation) for potable water services.

Please visit our website: www.lascofittings.com

