


## SCH 80 CPVC




Tee				
Part No	Size (in)	L	H	G
9801-005	½	2 13/16	1 3/8	1/2
9801-007	¾	3 1/8	1 9/16	9/16
9801-010	1	3 3/4	1 7/8	3/4
9801-012	1¼	4 11/32	2 5/32	15/16
9801-015	1½	4 13/16	2 3/8	1
9801-020	2	5 9/16	2 3/4	1 1/4
9801-025	2½	6 1/2	3 1/4	1 1/2
9801-030	3	7 13/32	3 11/16	1 13/16
9801-040	4	9 5/8	4 13/16	2 1/2
9801-060	6	13	6 1/2	3 1/2
9801-080	8	17 1/4	8 5/8	4 17/32

### Limited Warranty

LASCO Fittings, Inc. products are warranted to be free from manufacturing defects in materials and workmanship. They are warranted against rot, rust, and electrolytic corrosion for a period of three years from date of installation. If LASCO products prove defective due to manufacturing defects in material or workmanship during that period, the manufacturer will provide new replacement units of the same type and size. No remedy will be granted under this warranty if LASCO products are not used strictly in accordance with LASCO's directions with respect to use and storage or if the products have been modified in any way.

THE MANUFACTURER'S LIABILITY UNDER EXPRESSED OR IMPLIED WARRANTY OR FOR ANY REASON IS LIMITED TO FURNISHING REPLACEMENT UNITS OR GRANTING A CREDIT FOR DEFECTIVE UNITS. NO LABOR EXPENSE OR CONSEQUENTIAL DAMAGES WILL BE PAID BY LASCO. THIS WARRANTY IS IN LIEU OF ALL OTHER GUARANTEES AND WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PURPOSE, EXCEPT FOR ANY WARRANTIES IMPLIED BY LAW FOR NONCOMMERCIAL CONSUMERS. ANY SUCH WARRANTIES ARE LIMITED TO THE DURATION OF THIS WRITTEN WARRANTY.

DO NOT USE LASCO FITTINGS FOR COMPRESSED AIR OR GASES.  
DO NOT TEST PVC PIPING SYSTEMS WITH COMPRESSED AIR OR GASES.  
DO NOT USE FITTINGS WITH LIQUIDS NOT RECOMMENDED BY LASCO.  
MODIFICATIONS OF FITTINGS VOIDS THE WARRANTY.



### STANDARDS AND SPECIFICATIONS – SCHEDULE 80 CPVC

- ASTM D-1784 – Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly Vinyl Chloride) (CPVC) Compounds.
- ASTM F 437 – Threaded Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Pipe Fittings, Schedule 80.
- ASTM F 439 – Socket Type Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Pipe Fittings, Schedule 80.
- MATERIAL – LASCO Schedule 80 CPVC Fittings are produced from rigid Type IV, Grade I CPVC compound having a minimum Cell Classification of 23447 per ASTM D1784. O-Rings are produced from a Fluorocarbon Elastomer (VITON).
- LISTINGS – NSF (National Sanitation Foundation) listed for potable water service (NSF Std 61 & Std 14 as applicable).

Contact LASCO Technical Services for additional information regarding applicable standards and specifications: [TechnicalServices@lascofittings.com](mailto:TechnicalServices@lascofittings.com)

Please visit our website: [www.lascofittings.com](http://www.lascofittings.com)