

Rotary peelers



Rotary Peeler RS

Note:

This innovative Rotary Peeler RS is designed to use for universal peeling at the pipe end, for electrofusion couplings, tees and elbows and as well as for electrofusion saddles. Suitable for peeling of pipes made out of PE 80, PE 100, PEX, PP.

d (mm)	Article	Code	Weight (kg)
40	RS 40	790 136 001	2.340
50	RS 50	790 136 002	2.115
63	RS 63	790 136 003	2.090
75	RS 75	790 136 004	2.350
90	RS 90	790 136 005	2.460
110	RS 110	790 136 006	2.430
125	RS 125	790 136 007	3.895
140	RS 140	790 136 008	3.890
160	RS 160	790 136 009	3.790
180	RS 180	790 136 010	4.150
200	RS 200	790 136 011	3.995
225	RS 225	790 136 012	3.935
250	RS 250	790 136 013	5.575
280	RS 280	790 136 014	5.440
315	RS 315	790 136 015	5.380



Replacement blade to Rotary Peeler RS

d-d (mm)	Description	Code	Weight (kg)
40 - 315	Hard metal	790 136 100	0.013



Transport cases for Rotary Peeler RS

- Included in the scope of delivery of the Rotary Peeler RS

Article	Code	Weight (kg)	Dimension (mm)	Description
RSTC 40-63	790 136 221	0.718	343 - 277 - 125	for RS 40-RS 63
RSTC 75-110	790 136 222	0.870	343 - 277 - 125	for RS 75-RS 110
RSTC 125-160	790 136 223	0.870	490 - 400 - 153	for RS 125-RS 160
RSTC 180-225	790 136 213	1.796	450 - 360 - 132	for RS 180-RS 225
RSTC 250-315	790 136 214	2.901	566 - 435 - 156	for RS 250-RS 315



Rotary peeling tool RST 1000

- The flexible peeling tool RST 1000 is suitable for preparing welding zones of saddle and coupler jointings for Electrofusion fittings
- To ensure the constant removal of the oxidation layer for PE80 and PE100, a long lasting peeling blade made of carbide is used
- Easy-to-hinge chain links enable the staged operation of pipes d250 to d1000 mm
- Compensation for ovality and variable pipe diameters with loaded spring component in the chain
- Scope of delivery includes: various chain links, spare blade, transport box
- Size transport box = 58 x 48 x 15cm

d-d (mm)	Code	Weight (kg)
250 - 1000	799 300 799	10.552