


RING HANGERS

RING HANGER



- **Function:** Designed for the suspension of non-insulated stationary pipe lines. The knurled insert nut that allows a vertical adjustment after installation.
- **Material:** Carbon steel
- **Finish:** Electro-galvanized (10"-12"), Pre-galvanized (1/2"-8")
- **Approvals:** Underwriters' Laboratories Listed in the U.S. (UL), Canada (CUL), for use with standard steel pipe sizes 1/2" to 12". Factory Mutual Approved for steel pipe sizes 3/4" to 12". Complies with Manufacturers' Standardization Society ANSI/MSS SP-58 (Type 10) which supersedes ANSI/MSS SP-69.
- **Maximum Temperature:** 343° C (650° F)
- **Ordering:** Specify size, Finish.

Item	Size	Kurled Insert Nut			A		B		C		D		Max. Rec. Load		
		mm	in	in	mm	in	mm	in	mm	in	mm	in	Lbs	Kg	N
GSD9	1/2"	M10	3/8-16UNC	3/8-16BSW	25.33	1.00	35.98	1.42	58.48	2.30	70.39	2.77	299	135	1334
GSD9	3/4"	M10	3/8-16UNC	3/8-16BSW	26.47	1.04	39.82	1.57	62.32	2.45	76.93	3.03	299	135	1334
GSD9	1"	M10	3/8-16UNC	3/8-16BSW	27.28	1.07	43.98	1.73	66.48	2.62	84.44	3.32	299	135	1334
GSD9	1 1/4"	M10	3/8-16UNC	3/8-16BSW	27.58	1.09	48.68	1.92	71.18	2.80	93.54	3.68	299	135	1334
GSD9	1 1/2"	M10	3/8-16UNC	3/8-16BSW	26.83	1.06	50.98	2.01	73.48	2.89	98.89	3.89	299	135	1334
GSD9	2"	M10	3/8-16UNC	3/8-16BSW	26.53	1.04	56.68	2.23	79.18	3.12	110.59	4.35	299	135	1334
GSD9	2 1/2"	M10	3/8-16UNC	3/8-16BSW	50.7	2.00	87.2	3.43	109.7	4.32	147.55	5.81	339	153	1512
GSD9	3"	M10	3/8-16UNC	3/8-16BSW	49.63	1.95	94.08	3.70	116.58	4.59	162.74	6.41	419	189	1868
GSD9	3 1/2"	M10	3/8-16UNC	3/8-16BSW	43.28	1.70	94.08	3.70	116.58	4.59	169.09	6.66	499	225	2224
GSD9	4"	M10	3/8-16UNC	3/8-16BSW	49.83	1.96	106.98	4.21	129.48	5.10	188.34	7.41	599	270	2668
GSD9	5"	M12	1/2-13UNC	1/2-12BSW	55.1	2.17	125.75	4.95	154.25	6.07	227.38	8.95	799	360	3558
GSD9	6"	M12	1/2-13UNC	1/2-12BSW	60	2.36	144.15	5.68	172.65	6.80	259.28	10.21	1059	477	4714
GSD9	8"	M12	1/2-13UNC	1/2-12BSW	72.45	2.85	182	7.17	210.5	8.29	322.75	12.71	1619	729	7205
GSD9	10"	M16	5/8-11UNC	5/8-11BSW	84.5	3.33	221	8.70	256	10.08	397	15.63	2339	1053	10408
GSD9	12"	M16	5/8-11UNC	5/8-11BSW	105.05	4.14	267	10.51	302	11.89	468.45	18.44	3159	1422	14055